







SpraySpy® Model LL450

SpraySpy® LabLine - Spray analysis for highest demands in R&D

SpraySpy® LabLine is the next step in droplet and spray analytics, which has long been awaited by the Research & Development community. SpraySpy® LabLine measures the individual size, velocity, opacity and kinetic energy of droplets, as well as the flux density of the spray.

The laser based system copes with highly demanding liquids, like automotive effect lacquers, coatings, or bondings - even with the latest application methods, such as ultrasonic atomizers, pneumatic atomizers or rotating bell atomizers.

Using the patented SpraySpy® technology, atomization in extremely challenging environments, such as explosive atmospheres can be analyzed. This provides new options in research and development and a new, in-depth insight into atomization. It increases your knowledge about the spray and therefore, the quality of your products, already in the development phase. Consequently, the ratio of rejected to accepted units and the production costs for your customers decrease.



SpraySpy® LabLine highlights:

- Single droplet measurement of size and velocity
- Characterization of the momentum and flux density
- Online measurement of the digital spray pattern
- Analysis of individual transparent and non-transparent drops
- Storage and analysis of all droplet events
- Easy-to-use without adjustment
- Suitable for explosive atmospheres (ATEX)

The SpraySpy®-Technology

The SpraySpy® technology is based on scattered light from a moving droplet or particle, illuminated by a light beam. The resulting scattered light is separated by the acquisition time into its individual scattering orders and registered by photodetectors. The characteristics of the scattering orders are correlated with the size, velocity, number and opacity of particles in each individual droplet. Therefore, the SpraySpy® technology is a direct counting measurement method.

SpraySpy® Case Studies

Automotive Coating: Rotary Bell Atomizer

= 250 NL/min

= 250 NL/min


= 150 mL/min


Operating parameters:

- Shaping air 1
- Shaping air 2
- Paint flow
- Rotationfrequency


Medium

- ency = 45,000 rpm
- = Base Coat











Velocity





Size of transparent vs. non-transparent



Digital Spray Pattern: Pneumatic Atomizer

Operating parameters:





SpraySpy® LabLine Model Specification

Model	SpraySpy® LabLine			
	LL350	LL450	LL450X	LL550
Measured parameters	Droplet size Droplet velocity Number of drops	Drop size Drop velocity Detection timeline Number of drops Drop momentum Drop flux density Drop transparency ratio		
Measurement range • Size • Velocity	> 1 µm < 100 m/s			
Conditions Expolsive Atmo- sphere (ATEX) HV-Application 	No		ATEX: Zone 1 & 2 Yes	
Repeatability • Drop size • Drop velocity • Number of drops	1,7% 0,6% 1,5%			
Drop characteristics	Transparent Transparent, Semi-transparent & Non-transparent			
Sampling rate	250 MS/s			
Interfaces	Ethernet, current loop, ProfiNet, others on request			
Detachable Measure- ment probe	No		Yes	No
Hardware sizeMeasurement probeProcessing unit	220 x 150 x 50 mm 600 x 482 x 222 mm	200 x 167 x 150 mm 600 x 482 x 222 mm		
Operating parameters Power supply IP-Class 	24 V / 4A IP 67 (Measurement probe)			

AOM-Systems - Your Partner for Smart Sprays

Since years, **AOM-Systems** (Advanced **O**ptical **M**easurement Systems) has been involved in droplet and Spray measurements. The company has developed into a renowned address for droplet and spray measurement technology. The development of an easy to use and ATEX conform measurement technology has had a major influence on droplet and spray analytics. The latest innovation from AOM-Systems, the integrated measurement of transparent and non-transparent droplets, makes the development of sprays even more efficient and sustainable.

AOM-Systems GmbH

Benzstrasse 4 / 64646 Heppenheim / Germany

info@AOM-Systems.com / www.AOM-Systems.com



SpraySpy® & SprayAl® are registered trademarks of AOM-Systems GmbH. The SpraySpy® & SprayAl® technologies are protected by international patents. The specifications in this document are subject to change without notice. The presented data can differ from the standard model and can include additional modules involving extra costs. Errors and omissions excepted. AOM-Systems shall not be liable for errors contained herein or for incidental or consequential damages in connection with the performance or use of this material. Copyright 2013-2025 by AOM-Systems GmbH all rights reserved.